


**Electrical Test:**

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 5 ohm max.
3. Insulation Resistance: 10M ohm min.
4. Hi-pot:300V DC/10ms



11	Wire Clip OD:7.3mm	2	pcs
10	TUBE BLACK #1.5mm THIN	0.032	m
9	HDMI 20# BALCK ABS JACKET	2	pcs
8	HDMI M TRANSPARENT DUST COVER	2	pcs
7	45P BLACK PVC	16	g
6	TRANSPARENT PE	3	g
5	TUBE BALCK #0.8mm THIN.	0.024	m
4	TUBE BALCK #2.0mm THIN.	0.08	m
3	HDMI 20# Shell aluminium alloy laser etching HDMI LOGO	2	pcs
2	HDMI M SOLDER TYPE,GOLD PLATED SHELL , BLACK INSULATION	2	pcs
1	(28#*1P+EAM)*5PCS+28#*4C+AL+7/0.127TC+80/0.12ALM(50%)OD:7.3mm WITH BLACK/YELLOW NET	10	M
NO.	DESCRIPTION	Q'TY	UNIT

TOLERANCE		
	INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

**rotronic**

11.04.5506

ROLINE GOLD HDMI Cable, w/Ethernet, A M / A M  
10m, black w/yellow & black nylon net

DRAWN BY  
CHECK BY  
APPD BY

SCALE NONE  
UNIT MM  
DATE 2013.07.26

DRAWING NO.:  
REV. A  
1/1