


**Electrical Test:**

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 5 ohm max.
3. Insulation Resistance: 10M ohm min.
4. Hi-pot:300V DC/10ms



11	Wire Clip OD:7.3mm	2	pcs
10	TUBE BLACK #1.5mm THIN	0.032	m
9	HDMI 20# BALCK ABS JACKET	2	pcs
8	HDMI M TRANSPARENT DUST COVER	2	pcs
7	45P BLACK PVC	16	g
6	TRANSPARENT PE	3	g
5	TUBE BALCK #0.8mm THIN.	0.024	m
4	TUBE BALCK #2.0mm THIN.	0.08	m
3	HDMI 20# Shell aluminium alloy laser etching HDMI LOGO	2	pcs
2	HDMI M SOLDER TYPE,GOLD PLATED SHELL , BLACK INSULATION	2	pcs
1	(1P*26#+EAM)*5+4C*26#+AEB(50%AL) OD:8.5mm WITH BLACK/YELLOW NET	15	M
NO.	DESCRIPTION	Q'TY	UNIT

TOLERANCE	INCHES		M/M	
	.X	.015	.30	.10
	.XX	.010	.10	.05
.XXX	.005	.05		

rotronic

11.04.5508

ROLINE GOLD HDMI Cable, w/Ethernet, A M / A M  
15m, black w/yellow & black nylon net

DRAWN BY		SCALE	NONE	DRAWING NO.:	REV. A
CHECK BY		UNIT	MM		
APPD BY		DATE	2013.07.26		1/1