

1

2

3

4

5

6

length±xxmm

PLUG A

PIN.8

PIN.1

PLUG B

PIN.1

PIN.8

6.6±0.1

21.2±0.3

24.0±0.3

12.0±0.1

length mark

roline S/FTP PATCH CABLE 26AWG 4PR ISO/IEC 11801 & EN50288 CAT.6A LSOH XXXXXX-X

11.7±0.1

1

2

3

- (1)Jacket Color:White (RAL9003)
- (2)Wiring:T568B

item no.	length	tolerance
21.15.1970	0.5M	+20 -0
21.15.1971	1M	+20 -0
21.15.1972	2M	+20 -10
21.15.1973	3M	+20 -10
21.15.1975	5M	+30 -20
21.15.1976	7M	+30 -20
21.15.1977	10M	+30 -20
21.15.1978	15M	+30 -20
21.15.1979	20M	+70 -30

Specification :

Material :

- RJ45 Plug : (JE P/N : PUY8850)
 - Housing : Polycarbonate, UL 94V-2, Transparent color
 - Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated
 - Contact finished : Min. 50 micro-inch Gold plated on surface contact area
 - Shield : Bronze with Nickel plated
- SR : SR-V95 FOR S/FTP Boot with nose
- Cable :
 - Jacket : LSOH
 - Conductor : 26 AWG stranded copper
 - Isolation : PE
 - Shield : Aluminum Foil Shielded for Each Pair, copper clad with steel braid
- Cable structure : S/FTP, 4 twisted pair
- Minimum Banding Radius: 50mm

item no	21.15.1970	21.15.1971	21.15.1972	21.15.1973	21.15.1975
	21.15.1976	21.15.1977	21.15.1978	21.15.1979	

Desc ROLINE Cat 6a S/FTP Patch Cord,LSOH.Component Level,white

"#": Matching DIM.	DRAWING	25.Aug.2015	byz
"*": Important DIM.	CHECK	25.Aug.2015	Jane
Others General DIM.	APPROVAL	25.Aug.2015	Jaimy
		DATE	NAME

SECOMP

GENERAL TOLERANCE OF DIMENSIONS	SCALE	1/1 (A4)	UNIT	mm
X.XXX ±0.005				
X.XX ±0.05				
X.X ±0.1				

DRAWING NO.	
DRAWING CLASSIFICATION	S SHEET 1 OF 1

No.	MODIFIED AREA	ORIGINAL	MODIFY	DATE	MODIFIER

1

2

0

3

4

10cm

5

6

A1